

Catalog #	
Project:	
Type:	Date:
Notes:	

LED Explosion Proof - B & C Series



Key Features

- Can be used for both indoor & outdoor applications either as a high bay low bay or flood light
- Mounting: Pendant (3/4 NPT) | Pole | Yoke
Fixture can angle if required
- Beam Angle: 40°, 60°, 90° or 120°
- Lifespan: 50,000 (L70) Hours
- Weight: 26 Lbs

Optics

- CRI: 70+

Listings

- Color Temperature: 5K
- Operating Temperature Range: -40°F to 149°F
- IP Rating: IP66
- IK Rating: IK10

Electrical

- THD: ≤10%
- Power Factor: ≥0.95
- Operating Frequency 50/60Hz

Applications

- Where gas, vapors or dust are present
- Designed for hazardous environments in the oil, gas, chemical, food & alcohol processing

Model Number	Replaces	Length	Wattage	Lumens	Voltage
ML-60W-AN50D120	175W Metal Halide	12.5" X 9.5"X 6.5"	60W	8,400	100-277V or 277V-480V
ML-80W-AN50D120	250W Metal Halide		80W	11,200	
ML-100W-AN50D120			100W	14,000	
ML-150W-AN50D120	400W Metal Halide	14.9" X 9.1"X 10.6"	150W	21,000	
ML-200W-AN50D120		19" X 9"X 7.4"	200W	28,000	